DL7400

High Speed Printing
High Copy Ability
Straight Paper Path Route(Flat Bed)
Various Paper Path and
Several Paper Loading available
APTC and HCPP Function
Various Interface available

Evolving towards perfection

Large Table and Rear Stacker
(optional)

DL7400

FUJITSU

THE POSSIBILITIES ARE INFINITE

		DL7400
Printing Technology		Bi-directional with logical seeking in text and graphics mode
Print Head		24 wire, Impact Dot Matrix
Printing columns (10cpi)		136 column
Speed	Draft Quality	505cps (10cpi), 606cps (12cpi) *1
	Report Quality	240cps (10cpi), 288cps (12cpi)
	Letter Quality	120cps (10cpi), 144cps (12cpi)
Resolution		360 x 360 dpi (Maximum Graphics Resolution, Under ESC/P Emulation only)
Copy Ability		Original + 4carbonless copies (At High Copy Mode: Original + 7 carbonless copies)
Max. paper thickness		0.57mm (0.2244")
Paper feeding	Continuous Form	Push tractor - Front in, Rear out ; Rear in , Front out
	Cut Sheet	Front in, Front out ; Front in, Rear out ; Rear in, Front out ; Rear in, Rear out
Line Feed Speed		60ms per 1/6" line
Form Feed Speed		6" per second continuous feed
Continuous Form/Cut Sheet switch function		Manual/Auto
Paper thickness adjust function		Manual/Auto
Paper	Cut Sheet	Width	55~420mm (2.2 ~ 16.5 inch)
		Length	70~297mm (2.76~11.69 inch), (70~420mm (2.76~16.5 inch) for Large Cut Sheet Table)
	Continuous Form	Width	102~420mm (4.0~16.5 inches)
		Length	Over 102mm (Over 4.0 inches)
Interface	Parallel	IEEE1284 Nibble Mode
	USB	USB Ver.1.1 (TYPE B)
	Serial	RS232C 25pin
LAN (Optional card needed)		10BASE-T, 100 Base-TX , TCP/IP Protocol,
Emulation		Fujitsu DPL24C PLUS, Epson ESC/P2, IBM ®XL24E,
Character Sets		Code pages 437, 850, 851, 852, 855, 860, 862, 863, 865, 866, ISO 8859-1,ECMA 94, USA, UK, German, French, Italian, Spanish, Swedish, Finnish, Norwegian, Danish 1 and 2, Hungarian 1 and 2, Slovenian 1 and 2, Mazowia 1 and 2, Polish 1 and 2, Latin 2 1 and 2, Latin P, PG-DHN, Elot 927, Lithuanian 1 and 2, Mik, Macedonian, PG-MAC, ABY, ABG, DEC GR, GREEK 11, HBR-OLD, HBR-DEC, ISO Turkish, ISO Latin, Kamenicky 1 and 2, Turkish 1 and 2, Elot 928, Cyrillic, RUSCII, Latin-9, Spanish1, Spanish2, Japan, Latin A, KOREA, LEGAL, Windows Code Page 1250, Windows Code Page 1251, Windows Code Page 1252, IBM437, IBM851
Barcode		Code 3 of 9, UPC Type A, UPC Type A with check character, Codabar(NW7), EAN13, EAN8, Industrial 2 of 5, Matrix 2 of 5, Interleaved 2 of 5, Code 128
Resident Fonts		Bitmap font : Courier 10, Prestige Elite12, Boldface PS, Compressed, Draft 12, High-speed draft 12, OCR-B 10, OCR-A 10, Correspondence 10, PICA10 Scalable font : Courier, Nimbus Sans®, Timeless (Normal, Bold, Italic)
Input Buffer		Max. 128KB
Input Voltage		100V AC to 120V AC ±10%, single phase, 50Hz to 60Hz 220V AC to 240V AC ±10%, single phase, 50Hz to 60Hz
Consumption Power	Waiting	10W or less
	Average	90W or less
	Max.	180W
Environmental Conditions		5℃ to 38℃ (41°F to 100°F), 20~80%RH
Dimension	(WxDxH)	600 x 350 x 290mm (23.62 x 13.78 x 11.42inch)
Weight		Approximately 17Kg (37lbs)
Noise		59dBA

Model		Parallel + USB Model (LAN Upgradeable)
		Parallel + RS232C Model

Option		Cut Sheet Feeder (should be used with Rear Stacker)
		LAN Card
		Rear Stacker
		Large Cut Sheet Table
		Tractor

Reliability	MTBF	20,000H(25% duty cycle)
	MTTR	0.5H
	Printer Life	5 million Line-Feed or 5 years
Print Head	Print Head Life	400million strokes (each wire)
Ink Ribbon	Ribbon Life (Black)	5 million characters (ANK Draft Quality)
Safety and EMI standard		For Europe , North America and Asia Pacific
Environment	Fujitsu Green Product	Conformance

*1 Some letters cannot be printed at this speed.   (505CPS at 10CPI)

◆**High Speed Printing**
High Speed Printing as 606cps (12cpi,Draft Quality)

◆**High Copy Ability**
Maximum original +7 multiple copy sheet is able to be printed

◆**Straight Paper Path Route (Flat Bed)**
The Straight Paper Path Route enables paper to be fed smoothly. As paper does not need to be bent, there will be no discrepancy between top sheet and bottom sheet of multiple copy sheet and LF Accuracy is improved.

◆**Various Paper Path & Several Paper Loading available**
8 paper paths are available, of which up to 4 paper can be loaded at the same time. Utilising multiple paper paths enables various kinds of paper usage in a limited paper setting area and limited paper out condition.

Various Paper Paths   Several Paper Loading

◆**APTC and HCPP Function**
Detecting paper thickness, adjusting Head Gap automatically (APTC) ,and changing paper paths can be handled through the host by using Application Software or Windows Driver even if several paper forms are loaded at the same time.(HCPP)

◆**Various Interface available**
Parallel,RS232C,USB Interface and Optional LAN Card available

We care for theEarth.
This mark has been indicated to Fujitsu Isotec Green Product conformed to its internal standard

ENERGY STAR Compliance
As an ENERGY STAR Partner,Fujitsu Isotec Ltd.Has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

06.11-01